

# STEEL

## Project Fact Sheet



## REMOVAL OF RESIDUAL ELEMENTS IN THE STEEL LADLE

### BENEFITS

- Provide a method to remove/control undesirable residual elements, such as tin, contained in the steel ladle, thereby, increasing the flexibility of charge materials into the steelmaking furnace
- Increase the amount of steel scrap that can be recycled, thereby, improving the environment and reducing steelmaking costs
- Provide a method to improve the quality of steel contained in the steel ladle, thereby, increasing its potential applications

### APPLICATIONS

The project will develop a model of the deep injection process that includes absorption of reaction products by slag.

The model development will provide an operational method and control capability for improving the quality of molten steel produced by the steel industry. The added control/removal capability could be adopted by existing and planned ladle metallurgy stations in the steel industry.

## DEVELOPMENT OF THE DEEP INJECTION PROCESS CONTROL MODEL WILL IMPROVE STEELMAKING FLEXIBILITY AND STEEL QUALITY

The U.S. Department of Energy is partnering with the steel industry to develop processes to improve steel production efficiency. The steel industry uses scrap and other recycled materials, in addition to iron-ore based metallic materials, to produce molten steel for downstream processing. A good portion of the undesirable residual elements in liquid steel can originate from the recycled materials. Careful selection of charge materials to the steelmaking furnace is necessary to minimize and control these residual elements at acceptable levels. Steelmaking furnaces currently produce about 100 million tons of liquid steel that is all handled via steel ladles for further processing. The total annual value of steel handled by steel ladles is approximately \$22 billion. Developing methods to improve the consistency and efficient operation of the steelmaking furnaces is of unquestioned value to the steel industry. Control of the quality of molten steel delivered by steel ladles is an extremely important requirement for profitable steel mill operations. Consistent delivery of the molten steel free from undesirable residual elements is a key requirement.

### LADLE METALLURGY FURNACE



**Removal of residual elements from molten steel will lead to greater efficiency and productivity.**



## The Development of the Deep Injection Model (Continued)

The project will employ calcium injection to ensure an extremely low local oxygen potential and rapid reaction kinetics, in combination with a top slag to absorb the reaction products and hold those products without any significant reversion back to the steel bath. The focus of this work will be on feasibility of tin removal and ultimately to develop a process that will allow a greater portion of scrap with tin content to be used for steel production.

This project aims to develop: 1) a method to remove/control undesirable residual elements, such as tin, contained in a steel ladle, thereby, providing flexibility of charge materials into the steelmaking furnace; 2) increased recycling of steelmaking metallic materials, thereby, improving the environment and reducing steelmaking costs; and 3) provide a method to improve the quality of steel contained in the steel ladle, thereby, increasing its potential applications.

### Project Description

**Goal:** There are two primary objectives of this project: 1) to develop a process model from experimental kinetic data from injection experiments and information gathered on the rate of reversion from the top slag; and 2) to propose steel mill field tests, based on the results of studies carried out, to demonstrate the process capability.

### Progress and Milestones

- Project start date, February 1998.
- Completed partition tests with tin.
- Completed setting-up and testing of equipment to conduct injection studies in small scale melts and completed tin removal experiments; 50 percent of the tin was removed during the removal experiments.
- Field testing at a steel mill is planned and completion is expected in March 2001.
- Dissemination of results through the Iron and Steel Society conference is anticipated in November 2001.
- Final report is expected in April 2001.
- Project completion date, April 2001.



### PROJECT PARTNERS

McMaster University  
Department of Materials Science and  
Engineering  
Ontario, Canada  
(Principal Investigator)

American Iron and Steel Institute  
Washington, DC  
(Project Manager)

Dofasco, Inc.  
Ontario, Canada

U.S. Steel Research  
Monroeville, PA

Weirton Steel Corporation  
Weirton, WV

### FOR ADDITIONAL INFORMATION, PLEASE CONTACT:

Gobind Jagtiani  
Office of Industrial Technologies  
Phone: (202) 586-1826  
Fax: (202) 586-3237  
gobind.jagtiani@ee.doe.gov  
<http://www.oit.doe.gov/steel>

Please send any comments,  
questions, or suggestions to  
[webmaster.oit@ee.doe.gov](mailto:webmaster.oit@ee.doe.gov).

Visit our home page at  
[www.oit.doe.gov](http://www.oit.doe.gov).

Office of Industrial Technologies  
Energy Efficiency  
and Renewable Energy  
U.S. Department of Energy  
Washington, D.C. 20585



February 2001